

PCT/PTO 14 DEC 2004

10/517932

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
WO 2004/001276 A1

(51) International Patent Classification: F16L 55/163 // 55/1645

(21) International Application Number:  
PCT/SE2003/000994

(22) International Filing Date: 13 June 2003 (13.06.2003)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0201889-3 20 June 2002 (20.06.2002) SE

(71) Applicant and

(72) Inventor: EDSTRÖM, Sten [SE/SE]; N. Grönskärsvägen 5, S-804 29 Gävle (SE).

(74) Agents: OLSSON, Jan et al.; Bjerkens Patentbyrå KB, Box 1274, S-801 37 Gävle (SE).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD FOR SEALING AND/OR RECONDITIONING OF PIPES



(57) Abstract: In a method for sealing and/or reconditioning of pipes through spraying a fluid coating material towards the inner wall of the pipe at least one material piece (10) divided in the longitudinal direction thereof held together under pretension through means (11) to a pipe piece (17) with an outer diameter being less than the inner diameter of the pipe is before the spraying introduced into the pipe to a location for a substantial hole (12) in the pipe wall for covering the hole. The means for holding it together is then broken so that the pipe piece will bear under pretension against the inner wall of the pipe and form an auxiliary wall over the hole retaining the material sprayed inside the pipe.

BEST AVAILABLE COPY